



EXCELLENT PRINTABLE PRODUCTS

# TECHNICAL DATA SHEET

## **Synplas PET 50 UV S/A**

### **Product Description**

Synplas PET 50 UV S/A is a 50 micron optically clear PET film, with a solvent acrylic adhesive and a 36 micron clear (not optically clear) siliconised PET release line. The printable face of the media is optimised for UV printing.

### **Typical Applications**

Recommended for use in

- Window Graphics
- Point of Sale
- Outdoor Signage
- Internally illuminated Backlits

### **Key Features**

Synplas PET 50 UV S/A has a solvent acrylic medium tack adhesive, that is cleanly removable for up to 6 months after application.

It is suitable for Wet method application to flat glass or acrylic surfaces only. Application surfaces should be thoroughly cleaned prior to installation.

### **Sizes Available**

Maximum width of 1524mm in roll form with chosen length.

Sheet sizes can be tailored to customer requirements.

## **Properties**

Base Film Thickness	50 ± 3	μ	Micrometer
Total Thickness	106 ± 5	μ	Micrometer

## **Ink Compatibility**

Synplas PET 50 UV S/A is for UV inks only.

## **Storage**

When stored in a dry, well ventilated area, under ambient conditions, with no excessive variation in temperature, the useable life of the product should be in excess of 5 years.

114, Roebuck Road,  
Chessington Industrial Estate,  
Chessington,  
Surrey, KT9 1EU.  
**T: 01737 813517**

Unit 4, Rokeby Court,  
Warrington Road,  
Manor Park,  
Runcorn, WA7 1RW.  
**T: 01928 597750**

Email: [sales@depltd.co.uk](mailto:sales@depltd.co.uk)

Website: [www.depltd.co.uk](http://www.depltd.co.uk)



*To the best of our knowledge the information contained in this document is accurate. Suggestions concerning uses and applications are only the opinion of DEP Ltd and users should carry out their own testing procedures to confirm suitability for their purposes. DEP Ltd, does not assume liability for the accuracy or completeness of this information.*