

ASTRASTEN GREEN 3 STENCIL FILM

Detailed Description

Astrasten Green 3 consists of a 40µm green membrane coated onto a 75µ polyester base to give strength and durability as a low tack masking film. The stencil can be hand or machine cut. The membrane is formulated specifically to allow easy cutting and weeding.

Application

Cutting of stencil: Use a sharp cutter blade with minimum pressure to produce a clean cut for weeding.

Stencil application: Astrasten is adhered to the screen using Astrasten Green Activator and a roller, providing excellent adhesion to nylon and polyester mesh. Astrasten Green is a solvent activated stencil, therefore suitable for use with all water based screen process inks. It is designed to withstand water based screen washes, allowing the stencil to be re-used. Its durability allows long runs to be achieved. Removal of the stencil is simply accomplished by spraying solvent through the screen, releasing the stencil from the mesh and leaving it free from residue.

For step by step application instructions: Please refer to our Leaflet "From Computer to Screen in just 20 minutes."

Handling and Storage

The film should be stored in a dry and cool environment (12° - 25°) in the original packaging to avoid creasing.

114, Roebuck Road,
Chessington Industrial Estate,
Chessington,
Surrey, KT9 1EU.
T: 01737 813517

Unit 4, Rokeby Court,
Warrington Road,
Manor Park,
Runcorn, WA7 1RW.
T: 01928 597750

Email: sales@depltd.co.uk
Website: www.depltd.co.uk



To the best of our knowledge the information contained in this document is accurate. Suggestions concerning uses and applications are only the opinion of DEP Ltd and users should carry out their own testing procedures to confirm suitability for their purposes. DEP Ltd, does not assume liability for the accuracy or completeness of this information.