



EXCELLENT PRINTABLE PRODUCTS

TECHNICAL DATA SHEET

Synplas PP 180 VC Matte

Product Description

Synplas PP 180 VC Matte is a 180 micron extruded white polypropylene film, with a specially formulated inkjet receptive coating designed for eco-solvent, latex and UV Inks.

Typical Applications

Recommended for use in

- Banners
- Posters
- POS
- Roll Ups

Key Features

Synplas PP 180 VC Matte has the look of paper, but with the strength of PP, has a high tear resistance in both directions. Its coating has excellent chemical and water resistance and offers excellent imaging quality and high colour gamut. It can be punched, stitched, eyeleted, glued and creased.

Sizes Available

914mm x 30m

1270mm x 30m

Properties

Base Film Thickness		180 ± 3	μ	Micrometer
Total Thickness		197 ± 5	μ	Micrometer
Opacity (base)		>92	%	ISO 2471
Gloss		2.6	% @ 60 degrees	BYK Gardner
Thermal Shrinkage	MD	0.51	%	STM D-273
	CD	0.09	%	
Elongation	MD	118	%	ASTM D-882
	CD	52	%	

Ink Compatibility

Synplas PP 180 VC Matte is compatible with eco-solvent, latex and UV inks.

Storage

The material should be kept in its original packaging and stored in clean dry conditions ideally at 20 degrees C and 50% relative humidity.

114, Roebuck Road,
Chessington Industrial Estate,
Chessington,
Surrey, KT9 1EU.
T: 01737 813517

Unit 4, Rokeby Court,
Warrington Road,
Manor Park,
Runcorn, WA7 1RW.
T: 01928 597750

Email: sales@depltd.co.uk

Website: www.depltd.co.uk



COATING EXCELLENCE

To the best of our knowledge the information contained in this document is accurate. Suggestions concerning uses and applications are only the opinion of DEP Ltd and users should carry out their own testing procedures to confirm suitability for their purposes. DEP Ltd, does not assume liability for the accuracy or completeness of this information.