



EXCELLENT PRINTABLE PRODUCTS

TECHNICAL DATA SHEET

Synplas PET 50 UV S/A LO-Tac

Product Description

Synplas PET 50 UV Self Adhesive is a 50 micron optically clear PET film, with a low tack solvent acrylic adhesive and a clear siliconised PET release liner. The printable face of the media is optimised for UV printing of graphics.

Typical Applications

Recommended for use in

- Window Graphics
- Point of Sale
- Outdoor Signage
- Internally illuminated Backlits

Key Features

Synplas PET 50 UV S/A LO-TAC has a solvent acrylic low tack removable adhesive, that is cleanly removable for up to 6 months after application to glass surfaces.

It is suitable for Wet method application to flat glass or acrylic surfaces only. Application surfaces should be thoroughly cleaned prior to installation.

Sizes Available

Maximum width of 1524mm in roll form with chosen length.
Sheet sizes can be tailored to customer requirements.

Properties

Base Film Thickness	50 ± 3	μ	Micrometer
Total Thickness	106 ± 5	μ	Micrometer
Peel Test	5.23N	Newtons/ 25mm	FINAT method 1

Ink Compatibility

Synplas PET 50 UV S/A is for UV inks only.

Storage

When stored in a dry, well ventilated area, under ambient conditions, with no excessive variation in temperature, the useable life of the product should be in excess of 5 years.

114, Roebuck Road,
Chessington Industrial Estate,
Chessington,
Surrey, KT9 1EU.
T: 01737 813517

Unit 4, Rokeby Court,
Warrington Road,
Manor Park,
Runcorn, WA7 1RW.
T: 01928 597750

Email: sales@depltd.co.uk

Website: www.depltd.co.uk



To the best of our knowledge the information contained in this document is accurate. Suggestions concerning uses and applications are only the opinion of DEP Ltd and users should carry out their own testing procedures to confirm suitability for their purposes. DEP Ltd, does not assume liability for the accuracy or completeness of this information.