



TECHNICAL DATA SHEET

ASTRASHIELD ECONOMY 100 (WINDOW REPAIR FILM) – EM124

Product Outline

AstraShield Economy 100 is manufactured by DEP Ltd to the highest performance for adhesion to Glass .

Product Construction

Face film: The product is based on a strong 100 micron high clarity Polyester film.

Adhesive: The adhesive used is a high performance solvent acrylic with an optimized balance of tack, peel and shear. The coat weight is also optimized to ensure high impact performance.

Release liner: A gridded easy release paper liner has been selected for this product.

Application

Temporary Glass repair film. Cut film to cover complete window area; remove liner; apply to broken Window. If possible apply to both sides of window for added protection.

Sizes Available

Slit Width - 500mm & 1000mm

Roll Length – 3 Metres & 15 Metres

114, Roebuck Road,
Chessington Industrial Estate,
Chessington,
Surrey, KT9 1EU.
T: 01737 813517

Unit 4, Christleton Court,
Manor Park,
Runcorn.,
Runcorn, WA7 1ST
T: 01928 597750

Email: sales@depltd.co.uk
Website: www.depltd.co.uk



To the best of our knowledge the information contained in this document is accurate. Suggestions concerning uses and applications are only the opinion of DEP Ltd and users should carry out their own testing procedures to confirm suitability for their purposes. DEP Ltd, does not assume liability for the accuracy or completeness of this information.



Excellent Pre-Press Products

TECHNICAL DATA SHEET

ASTRASHIELD PREMIUM 175 (WINDOW REPAIR FILM) – EM015

Product Outline

AstraShield Premium 175 is a product certified to the highest impact test performance for Glass – 1B1.

Impact Test Clarification

The product has passed the test requirements for BS EN 12600 “Glass in Building – Pendulum Test - Impact Test Method and Classification for Flat Glass. Classification 1B1 – Highest possible

Product Construction

Face film: The product is based on an outstandingly strong 175 micron high clarity Polyester film.

Adhesive: The adhesive used is a high performance solvent acrylic with an optimized balance of tack, peel and shear. The coat weight is also optimized to ensure high impact performance.

Release liner: A gridded easy release paper liner has been selected for this product.

Application

Temporary Glass repair film. Cut film to cover complete window area; remove liner; apply to broken Window. If possible apply to both sides of window for added protection.

Sizes Available

Slit Width – 500mm, 1000mm

Roll Length – 3 Metres, 15 Metres.

114, Roebuck Road,
Chessington Industrial Estate,
Chessington,
Surrey, KT9 1EU.
T: 01737 813517

Unit 4, Christleton Court,
Manor Park
Runcorn,
WA7 1ST.
T: 01928 597750

Email: sales@depltd.co.uk
Website: www.depltd.co.uk



COATING EXCELLENCE

To the best of our knowledge the information contained in this document is accurate. Suggestions concerning uses and applications are only the opinion of DEP Ltd and users should carry out their own testing procedures to confirm suitability for their purposes. DEP Ltd, does not assume liability for the accuracy or completeness of this information.